

Maximum allowable loads for a given span length: **GS MW QA U80** module: 1000 mm

External cladding thickness [mm]:	0,6			
Internal cladding thickness [mm]:	0,6			
Outdoor temperature (summer / winter) [°C]:	55	65	80	-20
Indoor temperature (summer / winter) [°C]:	25		20	
Minimum width of end support [mm]:	40			
Minimum width of the intermediate support [mm]:	60			

The minimum number of screws on the end support:	2 + 1xPM-1
The minimum number of screws on the intermediate support:	2 + 1xPM-1
Core material:	MiWo
Cladding steel grade:	S220GD
Ultimate limit state (compare design loads)	ULS
Serviceability limit state (compare characteristic loads)	SLS

Static diagram	Color group	Criterion	Maximum evenly distributed load [kN / m ²]											
			Axial span of supports [m]											
			1,5	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	6,5	
Single-span arrangement	I	ULS	pressure	2,93	2,20	1,76	1,46	1,25	1,10	0,98	0,88	0,62	0,52	0,44
			suction	2,93	2,20	1,76	1,46	1,25	1,10	1,10	0,89	0,74	0,62	0,53
		SLS L/100	pressure	6,04	4,01	2,80	2,01	1,47	1,09	0,81	0,61	0,47	0,36	0,27
			suction	6,25	4,21	2,98	2,17	1,61	1,22	0,93	0,72	0,56	0,44	0,35
		SLS L/150	pressure	3,74	2,41	1,63	1,12	0,78	0,55	0,38	0,27	0,18	0,12	-
			suction	3,96	2,61	1,81	1,28	0,93	0,68	0,50	0,37	0,28	0,21	0,16
	II	ULS	pressure	2,60	1,61	1,04	0,68	0,44	0,28	0,17	-	-	-	-
			suction	2,81	1,81	1,22	0,84	0,59	0,41	0,29	0,20	0,14	-	-
		SLS L/100	pressure	2,93	2,20	1,76	1,46	1,25	1,10	0,98	0,88	0,62	0,52	0,44
			suction	2,93	2,20	1,76	1,46	1,25	1,10	1,10	0,89	0,74	0,62	0,53
		SLS L/150	pressure	6,04	4,01	2,80	2,01	1,47	1,09	0,81	0,61	0,47	0,36	0,27
			suction	6,04	4,01	2,80	2,01	1,47	1,09	0,81	0,61	0,47	0,36	0,27
	III	ULS	pressure	3,74	2,41	1,63	1,12	0,78	0,55	0,38	0,27	0,18	0,12	-
			suction	3,74	2,41	1,63	1,12	0,78	0,55	0,38	0,27	0,18	0,12	-
		SLS L/100	pressure	2,60	1,61	1,04	0,68	0,44	0,28	0,17	-	-	-	-
			suction	2,60	1,61	1,04	0,68	0,44	0,28	0,17	-	-	-	-
		SLS L/150	pressure	2,93	2,20	1,76	1,46	1,25	1,10	0,98	0,88	0,62	0,52	0,44
			suction	2,93	2,20	1,76	1,46	1,25	1,10	1,10	0,89	0,74	0,62	0,53
		SLS L/200	pressure	6,04	4,01	2,80	2,01	1,47	1,09	0,81	0,61	0,47	0,36	0,27
			suction	5,72	3,72	2,53	1,76	1,25	0,89	0,64	0,45	0,32	0,23	0,16
Multi-span arrangement	I	ULS	pressure	3,74	2,41	1,63	1,12	0,78	0,55	0,38	0,27	0,18	0,12	-
			suction	3,43	2,12	1,36	0,88	0,56	0,35	0,21	0,11	-	-	-
		SLS L/100	pressure	2,60	1,61	1,04	0,68	0,44	0,28	0,17	-	-	-	-
			suction	2,28	1,32	0,77	0,43	0,22	-	-	-	-	-	-
		SLS L/150	pressure	1,83	1,38	1,13	0,94	0,81	0,68	0,49	0,36	0,28	0,22	0,18
			suction	1,98	1,49	1,20	0,85	0,53	0,35	0,24	0,17	0,12	-	-
	II	ULS	pressure	6,31	4,41	3,29	2,55	2,05	1,65	1,33	1,09	0,90	0,75	0,63
			suction	6,48	4,55	3,41	2,66	2,14	1,72	1,41	1,15	0,96	0,80	0,67
		SLS L/100	pressure	3,97	2,74	2,03	1,56	1,25	0,98	0,79	0,64	0,52	0,43	0,35
			suction	4,15	2,89	2,15	1,67	1,34	1,06	0,86	0,71	0,58	0,48	0,40
		SLS L/150	pressure	2,80	1,91	1,39	1,06	0,85	0,65	0,52	0,41	0,33	0,26	0,21
			suction	2,98	2,05	1,52	1,17	0,94	0,74	0,59	0,48	0,39	0,32	0,26
	III	ULS	pressure	1,83	1,38	1,13	0,94	0,81	0,68	0,49	0,36	0,28	0,22	0,18
			suction	1,83	1,38	0,97	0,50	0,24	0,11	-	-	-	-	-
		SLS L/100	pressure	6,31	4,41	3,29	2,55	2,05	1,65	1,33	1,09	0,90	0,75	0,63
			suction	6,31	4,41	3,29	2,55	2,05	1,65	1,33	1,09	0,90	0,75	0,63
		SLS L/150	pressure	3,97	2,74	2,03	1,56	1,25	0,98	0,79	0,64	0,52	0,43	0,35
			suction	3,97	2,74	2,03	1,56	1,25	0,98	0,79	0,64	0,52	0,43	0,35
		SLS L/200	pressure	2,80	1,91	1,39	1,06	0,85	0,65	0,52	0,41	0,33	0,26	0,21
			suction	2,80	1,91	1,39	1,06	0,85	0,65	0,52	0,41	0,33	0,26	0,21
	III	ULS	pressure	1,83	1,38	1,13	0,94	0,81	0,68	0,49	0,36	0,28	0,22	0,18
			suction	1,60	0,84	-	-	-	-	-	-	-	-	-
		SLS L/100	pressure	6,31	4,41</td									

Maximum allowable loads for a given span length: GS MW QA U100 module: 1000 mm

External cladding thickness [mm]:	0,6			
Internal cladding thickness [mm]:	0,6			
Outdoor temperature (summer / winter) [°C]:	55	65	80	-20
Indoor temperature (summer / winter) [°C]:	25		20	
Minimum width of end support [mm]:	40			
Minimum width of the intermediate support [mm]:	60			

The minimum number of screws on the end support:	2 + 1xPM-1
The minimum number of screws on the intermediate support:	2 + 1xPM-1
Core material:	MiWo
Cladding steel grade:	S220GD
Ultimate limit state (compare design loads)	ULS
Serviceability limit state (compare characteristic loads)	SLS

Static diagram	Color group	Criterion	Maximum evenly distributed load [kN / m ²]											
			Axial span of supports [m]											
			1,5	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	6,5	
Single-span arrangement	I	ULS	pressure	4,38	3,29	2,63	2,19	1,88	1,64	1,15	0,94	0,77	0,65	0,55
			suction	4,38	3,29	2,63	2,19	1,88	1,74	1,37	1,11	0,92	0,77	0,66
		SLS L/100	pressure	7,46	5,09	3,66	2,71	2,05	1,57	1,22	0,95	0,75	0,59	0,47
			suction	7,66	5,29	3,84	2,88	2,20	1,71	1,34	1,07	0,85	0,69	0,56
		SLS L/150	pressure	4,70	3,14	2,20	1,59	1,16	0,86	0,64	0,48	0,36	0,27	0,20
			suction	4,90	3,33	2,38	1,75	1,32	1,00	0,77	0,59	0,46	0,36	0,28
	II	ULS	pressure	3,32	2,16	1,47	1,03	0,72	0,51	0,35	0,24	0,16	0,10	-
			suction	3,53	2,36	1,65	1,19	0,87	0,65	0,48	0,36	0,27	0,20	0,15
		SLS L/100	pressure	4,38	3,29	2,63	2,19	1,88	1,64	1,15	0,94	0,77	0,65	0,55
			suction	4,38	3,29	2,63	2,19	1,88	1,74	1,37	1,11	0,92	0,77	0,66
		SLS L/150	pressure	7,46	5,09	3,66	2,71	2,05	1,57	1,22	0,95	0,75	0,59	0,47
			suction	7,46	5,09	3,66	2,71	2,05	1,57	1,22	0,95	0,75	0,59	0,47
	III	ULS	pressure	4,70	3,14	2,20	1,59	1,16	0,86	0,64	0,48	0,36	0,27	0,20
			suction	4,70	3,14	2,20	1,59	1,16	0,86	0,64	0,48	0,36	0,27	0,20
		SLS L/100	pressure	3,32	2,16	1,47	1,03	0,72	0,51	0,35	0,24	0,16	0,10	-
			suction	3,32	2,16	1,47	1,03	0,72	0,51	0,35	0,24	0,16	0,10	-
		SLS L/150	pressure	4,38	3,29	2,63	2,19	1,88	1,64	1,15	0,94	0,77	0,65	0,55
			suction	4,38	3,29	2,63	2,19	1,88	1,74	1,37	1,11	0,92	0,77	0,66
		SLS L/200	pressure	7,46	5,09	3,66	2,71	2,05	1,57	1,22	0,95	0,75	0,59	0,47
			suction	7,15	4,81	3,39	2,47	1,82	1,36	1,03	0,78	0,59	0,45	0,34
Multi-span arrangement	I	ULS	pressure	4,70	3,14	2,20	1,59	1,16	0,86	0,64	0,48	0,36	0,27	0,20
			suction	4,40	2,85	1,93	1,34	0,94	0,65	0,45	0,31	0,20	0,12	-
		SLS L/100	pressure	3,32	2,16	1,47	1,03	0,72	0,51	0,35	0,24	0,16	0,10	-
			suction	3,02	1,88	1,20	0,78	0,49	0,30	0,16	-	-	-	-
		SLS L/150	pressure	2,40	1,79	1,44	1,22	1,06	0,94	0,69	0,52	0,39	0,31	0,25
			suction	2,52	1,89	1,52	1,22	0,77	0,51	0,35	0,25	0,18	0,14	0,11
	II	ULS	pressure	7,66	5,41	4,08	3,21	2,59	2,14	1,77	1,47	1,24	1,05	0,89
			suction	7,84	5,56	4,21	3,32	2,69	2,23	1,85	1,55	1,30	1,11	0,95
		SLS L/100	pressure	4,88	3,41	2,55	1,99	1,60	1,31	1,07	0,89	0,74	0,62	0,52
			suction	5,05	3,55	2,67	2,10	1,70	1,40	1,15	0,95	0,80	0,68	0,57
		SLS L/150	pressure	3,48	2,40	1,78	1,37	1,10	0,90	0,73	0,59	0,49	0,40	0,34
			suction	3,65	2,55	1,91	1,49	1,20	0,98	0,81	0,66	0,55	0,46	0,39
	III	ULS	pressure	2,40	1,79	1,44	1,22	1,06	0,94	0,69	0,52	0,39	0,31	0,25
			suction	2,39	1,79	1,44	0,80	0,45	0,24	0,12	-	-	-	-
		SLS L/100	pressure	7,66	5,41	4,08	3,21	2,59	2,14	1,77	1,47	1,24	1,05	0,89
			suction	7,66	5,41	4,08	3,21	2,59	2,14	1,77	1,47	1,24	1,05	0,89
		SLS L/150	pressure	4,88	3,41	2,55	1,99	1,60	1,31	1,07	0,89	0,74	0,62	0,52
			suction	4,88	3,41	2,55	1,99	1,60	1,31	1,07	0,89	0,74	0,62	0,52
		SLS L/200	pressure	3,48	2,40	1,78	1,37	1,10	0,90	0,73	0,59	0,49	0,40	0,34
			suction	3,48	2,40	1,78	1,37	1,10	0,90	0,73	0,59	0,49	0,40	0,34
Multi-span arrangement	III	ULS	pressure	2,40	1,79	1,44	1,22	1,06	0,94	0,69	0,52	0,39	0,31	0,25
			suction	2,20	1,64	0,4								

Maximum allowable loads for a given span length: GS MW QA U120 module: 1000 mm

External cladding thickness [mm]:	0,6			
Internal cladding thickness [mm]:	0,6			
Outdoor temperature (summer / winter) [°C]:	55	65	80	-20
Indoor temperature (summer / winter) [°C]:	25		20	
Minimum width of end support [mm]:	40			
Minimum width of the intermediate support [mm]:	60			

The minimum number of screws on the end support:	2 + 1xPM-1
The minimum number of screws on the intermediate support:	2 + 1xPM-1
Core material:	MiWo
Cladding steel grade:	S220GD
Ultimate limit state (compare design loads)	ULS
Serviceability limit state (compare characteristic loads)	SLS

Static diagram	Color group	Criterion	Maximum evenly distributed load [kN / m ²]											
			Axial span of supports [m]											
			1,5	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	6,5	
Single-span arrangement	I	ULS	pressure	4,80	3,60	2,88	2,40	2,06	1,80	1,60	1,13	0,93	0,78	0,66
			suction	4,80	3,60	2,88	2,40	2,06	2,09	1,65	1,34	1,10	0,93	0,79
		SLS L/100	pressure	8,50	5,92	4,35	3,30	2,55	2,00	1,59	1,27	1,03	0,83	0,68
			suction	8,69	6,10	4,52	3,46	2,70	2,14	1,72	1,39	1,14	0,93	0,77
		SLS L/150	pressure	5,42	3,71	2,67	1,98	1,50	1,15	0,89	0,69	0,54	0,42	0,33
			suction	5,61	3,89	2,84	2,15	1,65	1,29	1,02	0,81	0,65	0,52	0,42
	II	ULS	pressure	3,87	2,60	1,83	1,33	0,98	0,72	0,54	0,40	0,29	0,21	0,15
			suction	4,06	2,78	2,00	1,49	1,13	0,86	0,67	0,52	0,40	0,32	0,25
		SLS L/100	pressure	4,80	3,60	2,88	2,40	2,06	1,80	1,60	1,13	0,93	0,78	0,66
			suction	4,80	3,60	2,88	2,40	2,06	2,09	1,65	1,34	1,10	0,93	0,79
		SLS L/150	pressure	8,50	5,92	4,35	3,30	2,55	2,00	1,59	1,27	1,03	0,83	0,68
			suction	8,50	5,92	4,35	3,30	2,55	2,00	1,59	1,27	1,03	0,83	0,68
		III	pressure	5,42	3,71	2,67	1,98	1,50	1,15	0,89	0,69	0,54	0,42	0,33
			suction	5,42	3,71	2,67	1,98	1,50	1,15	0,89	0,69	0,54	0,42	0,33
			pressure	3,87	2,60	1,83	1,33	0,98	0,72	0,54	0,40	0,29	0,21	0,15
			suction	3,87	2,60	1,83	1,33	0,98	0,72	0,54	0,40	0,29	0,21	0,15
			pressure	4,80	3,60	2,88	2,40	2,06	1,80	1,60	1,13	0,93	0,78	0,66
			suction	4,80	3,60	2,88	2,40	2,06	2,09	1,65	1,34	1,10	0,93	0,79
Multi-span arrangement	I	ULS	pressure	8,50	5,92	4,35	3,30	2,55	2,00	1,59	1,27	1,03	0,83	0,68
			suction	8,22	5,65	4,09	3,06	2,33	1,80	1,40	1,09	0,86	0,68	0,54
		SLS L/100	pressure	5,42	3,71	2,67	1,98	1,50	1,15	0,89	0,69	0,54	0,42	0,33
			suction	5,13	3,44	2,41	1,74	1,28	0,94	0,69	0,51	0,37	0,27	0,19
		SLS L/150	pressure	3,87	2,60	1,83	1,33	0,98	0,72	0,54	0,40	0,29	0,21	0,15
			suction	3,59	2,33	1,58	1,09	0,75	0,51	0,34	0,22	0,13	-	-
	II	ULS	pressure	2,22	1,65	1,32	1,11	0,96	0,85	0,77	0,69	0,53	0,41	0,33
			suction	1,92	1,42	1,14	0,96	0,83	0,71	0,50	0,36	0,26	0,20	0,15
		SLS L/100	pressure	8,66	6,17	4,68	3,71	3,03	2,52	2,13	1,80	1,54	1,32	1,13
			suction	8,83	6,32	4,82	3,83	3,13	2,61	2,21	1,87	1,60	1,37	1,19
		SLS L/150	pressure	5,55	3,91	2,95	2,32	1,88	1,55	1,31	1,10	0,94	0,79	0,68
			suction	5,72	4,06	3,08	2,44	1,98	1,65	1,39	1,17	1,00	0,85	0,74
		SLS L/200	pressure	3,99	2,78	2,08	1,63	1,31	1,07	0,90	0,75	0,63	0,54	0,45
			suction	4,16	2,94	2,21	1,74	1,41	1,16	0,98	0,83	0,70	0,59	0,51
	III	ULS	pressure	2,22	1,65	1,32	1,11	0,96	0,85	0,77	0,69	0,53	0,41	0,33
			suction	2,22	1,65	1,32	1,11	0,68	0,42	0,24	0,13	-	-	-
		SLS L/100	pressure	8,66	6,17	4,68	3,71	3,03	2,52	2,13	1,80	1,54	1,32	1,13
			suction	8,66	6,17	4,68	3,71	3,03	2,52	2,13	1,80	1,54	1,32	1,13
		SLS L/150	pressure	5,55	3,91	2,95	2,32	1,88	1,55	1,31	1,10	0,94	0,79	0,68
			suction	5,55	3,91	2,95	2,32	1,88	1,55	1,31	1,10	0,94	0,79	0,68
		SLS L/200	pressure	3,99	2,78	2,08	1,63	1,31	1,07	0,90	0,75	0,63	0,54	0,45
			suction	3,99	2,78	2,08	1,63	1,31	1,07	0,90	0,75	0,63	0,54	0,45
	III	ULS	pressure	2,22	1,65	1,32	1,11	0,96	0,85	0,77	0,69	0,53	0,41	0,33
			suction	2,06	1,52	1,00	0,27	-	-	-	-	-		